STONE SPECIFICATION

Piles Creek - Guinea Gold









HOW TO SPECIFY

GENERAL: Sandstone shall be Piles Creek - Guinea Gold Sandstone by Gosford Quarries

STONE TYPE: Piles Creek - Guinea Gold Sandstone

COLOUR: Grey-Gold buff oxidizing sandstone. A 'Yellow Block' sandstone.

STONE FINISH: Diamond sawn, Gang sawn, Honed, Rockfaced, Sparrow pecked & Custom

SIZES: As specified by architect

FIXING: Adhesive Material to be compatible to substrate medium. Stone cladding above 2.3 metres in height to be mechanically fixed.

Refer to ASAA Natural Stone Design manual for more information.

SEALING: Sealer to be specified by designer or installer

TYPICAL TECHNICAL SPECIFICATION

BULK DENSITY (ASTM C97-83): 2.25 tonnes/m³

ABSORPTION BY WEIGHT (ASTM C97-83): 4.2 %

MODULUS OF RUPTURE:

8.0 MPa Dry, 3.9 MPa Wet

COMPRESSIVE STRENGTH (ASTM CI70-87):

65 MPa Dry, 40 MPa Wet



*Sandstone is a natural product and therefore subject to variation in colour, tone, shade and texture.

TERREY HILLS SHOWROOM

301 Mona Vale Road Terrey Hills NSW 2084 P 02 8585 8282

SOMERSBY SHOWROOM

70 Quarry Rd Somersby NSW 2250 P 02 4340 3000

CLAYTON SOUTH SHOWROOM

9 Prestige Drive Clayton South VIC 3169 P 03 9558 2283

BEAUDESERT SHOWROOM

1812 Beaudesert Boonah Rd, Allenview QLD 4285 P 07 5541 0143





